

Kleen-Plus®

AUTOMATIC BACKWASH PERMANENT FILTERS SELECTION GUIDE FOR DOMESTIC USE:

GUIDE ONLY - CONTACT APL FOR SPECIFIC SIZING DETAILS

PROBLEM	SMALL	MEDIUM	LARGE	HIGH CAPACITY
	Up to 20 lpm	Up to 30 lpm	Up to 40 lpm	50 lpm
SEDIMENT	SF 948H	SF 1054M	SF 1252T	SF 1465T
TASTE & ODOUR	CF 948H	CF 1054M	CF 1252T	CF 1465T
LOW pH 6-7	NF 948H	NF 1054M	NF 1252T	NF 1465T
VERY LOW pH <6	NF 1054H+	NF 1252M+	NF 1465T+	NF 1865T+
HARD WATER & LOW IRON	CWS 735T	WS 948T	CWS 1035T	WS 1252T
NITRATES	NR 735T	NR 948T	NR 1054T	NR 1252T
LOW IRON <4ppm & MANGANESE	OF 948H	OF 1052T	OF 1252T	OF 1465T
HIGH IRON AND MANGANESE	These systems are designed for each specific application – Send APL a water test and water usage data for analysis and design/quote			

PART SUFFIX DENOTES BACKWASH CONTROL STYLE

H	Manual start/stop	(180° handle)	¾" ports
M	Manual start - Automatic stop	(Time Clock)	¾" ports
T	Automatic start - Automatic stop	(12 day clock)	1" ports
E	Automatic start – Automatic stop	(Electronic)	1" ports
+	Special low pH media		

Please refer to individual specification pages for further details